VALUE UTP Patch Cord Cat.6A (Class EA), green, 0.5

m

| Product No. Manufacturer Manufacturer No. EAN (single piece) | 21.99.1440 VALUE 21.99.1440 7611990120659 | Value |
|---|---|-------|
| | $ \begin{array}{c} \hline \\ \hline $ | |



- The cheap solution for data transfer rates of up to 10 Gbit/s and a bandwidth of 500 MHz
- Patch cable for networking connections between devices
- Prepared shielded Twisted Pair cable (PiMF) with RJ-45 connectors on both ends.
- Durable due to moulded kink protection.
- Flexible cable, suitable for narrow bending.
- Impedance: 100 Ohm
- Contact settings 1:1, in accordance with the EIA/TIA 568 standard.
- Construction: 8 lines, pairs shielded with aluminium foil, complete shielding in tinned copper braid

For a structured shielded Cat.6a cabling system we recommend to use the following components:

VALUE Cat.6a UTP Cable, Solid Wire, 300 m: 21.99.1681 Flush Mount Wall Jack for Keystones: 25.16.8579 Surface Wall Mount Frame: 25.16.8484 VALUE Cat.6a Keystone, RJ-45, shielded: 26.99.0366 19" Keystone Patch Panel: 26.11.0358 / 26.11.0359 VALUE Cat.6a S/FTP Patch Cord, 5 m: 21.99.0875

| Technical specifications | | |
|----------------------------|--------------------|--|
| Manufacturer | VALUE | |
| Product group | Twisted Pair Cable | |
| Product type | UTP Patch Cables | |
| Colour | green | |
| Length | 0.5 m | |
| Shield type | UTP | |
| Transfer quality | Cat6A / Class EA | |
| Quantity of wires | 8 | |
| Conductor type | Wire | |
| Crossed | Νο | |
| Colour (Spout) | green | |
| Cable LSOH | Νο | |
| Side 1 Connector Type | RJ-45 | |
| Side 1 Connector Gender | Male | |
| Side 2 Connector Type | RJ-45 | |
| Side 2 Connector Gender | Male | |
| Connector Type RJ45 | Standard | |