

EAP Product List

Ceiling Mount 802.11ax AP

Picture			
Model	EAP660 HD	EAP620 HD	EAP610
Product	AX3600 Wireless Dual-Band Multi-Gigabit Ceiling Mount Access Point	AX1800 Ceiling Mount Wi-Fi 6 Access Point	AX1800 Ceiling Mount Wi-Fi 6 Access Point
Speed	2.4 GHz: 4*4 11ax, 1148 Mbps 5 GHz: 4*4 11ax, 2402 Mbps	2.4 GHz: 2*2 11ax, 574 Mbps 5 GHz: 2*2 11ax, 1201 Mbps	2.4 GHz: 2*2 11ax, 574 Mbps 5 GHz: 2*2 11ax, 1201 Mbps
Ethernet Port	1 x 2.5Gbps Ethernet Port	1 x Gigabit Ethernet Port	1 x Gigabit Ethernet Port
Power Supply	802.3at PoE / 12V DC	802.3at PoE / 12V DC	802.3at PoE / 12V DC
Internal Antennas	2.4 GHz: 4 x 4 dBi 5 GHz: 4 x 5 dBi	2.4 GHz: 2 x 4 dBi 5 GHz: 2 x 5 dBi	2.4 GHz: 2 x 4 dBi 5 GHz: 2 x 5 dBi

Ceiling Mount 802.11n/ac AP

Picture					
Model	EAP265 HD	EAP245	EAP225	EAP115	EAP110
Product	AC1750 Wireless MU-MIMO Gigabit Ceiling Mount Access Point	AC1750 Wireless MU-MIMO Gigabit Ceiling Mount Access Point	AC1350 Wireless MU-MIMO Gigabit Ceiling Mount Access Point	300Mbps Wireless N Ceiling Mount Access Point	300Mbps Wireless N Ceiling Mount Access Point
Speed	2.4 GHz: 450Mbps 5 GHz: 1300Mbps	2.4 GHz: 450Mbps 5 GHz: 1300Mbps	2.4 GHz: 450Mbps 5 GHz: 867Mbps	2.4 GHz: 300Mbps	2.4 GHz: 300Mbps
Ethernet Port	2 x Gigabit Ethernet Port	2 x Gigabit Ethernet Port	1 x Gigabit Ethernet Port	1 x 10/100Mbps Ethernet Port	1 x 10/100Mbps Ethernet Port
Power Supply	802.3af PoE / 48 V Passive PoE	802.3af PoE / 48 V Passive PoE	802.3af PoE / 24V Passive PoE	802.3af PoE / External 9 V/0.6 A DC power supply	24V Passive PoE
Internal Antennas	2.4 GHz: 3 x 3.5 dBi 5 GHz: 3 x 4 dBi	2.4 GHz: 3 x 3.5 dBi 5 GHz: 3 x 4 dBi	2.4 GHz: 3 x 4 dBi 5 GHz: 2 x 5 dBi	2 x 4 dBi	2 x 4 dBi

Specifications

Ceiling Mount 802.11ax AP

Model		EAP660 HD	EAP620 HD	EAP610
Name		AX3600 Wireless Dual-Band Multi-Gigabit Ceiling Mount Access Point	AX1800 Ceiling Mount Wi-Fi 6 Access Point	AX1800 Ceiling Mount Wi-Fi 6 Access Point
Main Design	LAN Interfaces	1 x 2.5Gbps Ethernet Port	1 x Gigabit Ethernet Port	1 x Gigabit Ethernet Port
	Wi-Fi Standards	IEEE 802.11ax/ac/n/g/b/a		
	Maximum Data Rate	1148 Mbps (2.4 GHz) +2402 Mbps (5 GHz)	574 Mbps (2.4 GHz) +1201 Mbps (5 GHz)	574 Mbps (2.4 GHz) +1201 Mbps (5 GHz)
	Concurrent Clients	1000+	1000+	250+
	Antennas	2.4 GHz: 4 x 4 dBi 5 GHz: 4 x 5 dBi	2.4 GHz: 2 x 4 dBi 5 GHz: 2 x 5 dBi	2.4 GHz: 2 x 4 dBi 5 GHz: 2 x 5 dBi
	Transmit Power	CE: < 20 dBm (2.4 GHz, EIRP); < 23 dBm (5 GHz, EIRP) FCC: < 26 dBm (2.4 GHz); < 26 dBm (5 GHz)	CE: < 20 dBm (2.4 GHz, EIRP); < 23 dBm (5 GHz, EIRP) FCC: < 25 dBm (2.4 GHz); < 25 dBm (5 GHz)	CE: < 20 dBm (2.4 GHz, EIRP); < 23 dBm (5 GHz, EIRP) FCC: < 25 dBm (2.4 GHz); < 25 dBm (5 GHz)
Centralized Management	Omada Software Controller	•		
	Omada Hardware Controller	•		
	Omada APP	•		
Security	Captive Portal Authentication	•		
	Access Control	•		
	Maximum number of MAC Filter	4000		
	Wireless Isolation between Clients	•		
	VLAN	•		
	Rogue AP Detection	•		
	Wireless Encryption	WPA-Personal/Enterprise, WPA2-Personal/Enterprise, WPA3-Personal/Enterprise		
	802.1X Support	•		
Wireless Function	Multiple SSIDs	16 (8 on each band)		
	Enable/Disable Wireless Radio	•		
	Enable/Disable SSID Broadcast	•		
	Guest Network	•		
	Automatic Channel Assignment	•		
	Transmit Power Control	Adjust transmit Power on dBm		
	QoS (WMM)	•		
	Seamless Roaming	•		
	Mesh	-	•(*)	•
	Beamforming	•		
	MU-MIMO	•		
	Rate Limit	Based on SSID/Client		
	Load Balance	•		
	Airtime Fairness	•		
	Band Steering	•		
	RADIUS Accounting	•		
	MAC Authentication	•		
	Reboot Schedule	•		
	Wireless Schedule	•		
	Wireless Statistics	•		
Static IP/Dynamic IP	•			

* EAP620 HD v2.0 supports Mesh; EAP620 HD v1.0 will support Mesh with later firmware in future.

Ceiling Mount 802.11ax AP

Model		EAP660 HD	EAP620 HD	EAP610
Support Data Rates	802.11ax	8 Mbps to 2402 Mbps (MCS0-MCS11, NSS = 1 to 4 HE20/40/80)	8 Mbps to 1201 Mbps (MCS0-MCS11, NSS = 1 to 2 HE20/40/80)	8 Mbps to 1201 Mbps (MCS0-MCS11, NSS = 1 to 2 HE20/40/80)
	802.11ac	6.5 Mbps to 2166.7 Mbps (MCS0-MCS11, NSS = 1 to 4 VHT20/40/80)	6.5 Mbps to 1083.3 Mbps (MCS0-MCS11, NSS = 1 to 2 VHT20/40/80)	6.5 Mbps to 1083.3 Mbps (MCS0-MCS11, NSS = 1 to 2 VHT20/40/80)
	802.11n	6.5 Mbps to 600 Mbps (MCS0-MCS31, HT20/40)	6.5 Mbps to 300 Mbps (MCS0-MCS15, HT20/40)	6.5 Mbps to 300 Mbps (MCS0-MCS15, HT20/40)
	802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps		
	802.11b	1, 2, 5.5, 11 Mbps		
	802.11a	6, 9, 12, 18, 24, 36, 48, 54 Mbps		
Management	LED ON/OFF Control	•		
	Management MAC Access Control	•		
	Web-based Management	•		
	Telnet	•		
	SNMP	v1, v2c, v3		
	SSH	•		
	Restore & Backup	•		
	Firmware update via Web	•		
	NTP	•		
	System Log	•		
Email Alerts	•			
Physical & Environment	Power Supply	802.3at PoE or external 12V/2A DC power supply	802.3at PoE or external 12V/1A DC power supply	802.3at PoE or external 12V/1A DC power supply
	Maximum Power Consumption	EU: 18.5 W (For PoE); 15 W (for DC) US: 22.5 W (For PoE); 18 W (for DC)	EU: 12.5 W (For PoE); 10 W (for DC) US: 14W (For PoE); 11.5 W (for DC)	EU: 12.8 W (For PoE); 10.8 W (for DC) US: 13.9W (For PoE); 11.8 W (for DC)
	Reset	•		
	Mounting	Ceiling / Wall mouting (Kits included)		
Others	Certifications	CE, FCC, RoHS		
	Dimensions (W x D x H)	243 x 243 x 64 mm		
	Environment	Operating Temperature: 0 °C–40 °C (32 °F–104 °F); Storage Temperature: -40 °C–70 °C (-40 °F–158 °F); Operating Humidity: 10%–90% non-condensing; Storage Humidity: 5%–90% non-condensing;		

