

Specifications

Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x,
Protocol	CSMA/CD
Interface	16 10/100Mbps ports, Auto-Negotiation, Auto MDI/MDIX
Switching Features	Half and Full Duplex MAC Address Learning 3.2 Gbps Switching Capacity
Forwarding Rates	10BASE-T: 14880pps/port 100BASE-TX: 148800pps/port
Data Rates	10/100Mbps at Half Duplex 20/200Mbps at Full Duplex
LEDs	Power, Ethernet Ports(1-16)
Transfer Method	Store and Forward
Power Supply	External Power Adapter (Output: 9V/0.6A)
Certifications	CE, FCC, RoHS
Dimensions	7.9 x 5.6 x 1.6 in. (200 x 142 x 40 mm)
Operating Temperature	0°C to 40 °C (32 °F to 104°F)
Storage Temperature	-40 °C to 70 °C (-40 °F to 158°F)
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 90% non-condensing

www.tp-link.com

Specifications are subject to change without notice. TP-Link is a registered trademark of TP-Link Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. Copyright © 2017 TP-Link Technologies Co., Ltd. All rights reserved.