

Specifications

Model	TL-POE150S
Standards	IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3af
Ports	1 10/100/1000Mbps Auto-Negotiation RJ45 LAN port(LAN IN) 1 10/100/1000Mbps Auto-Negotiation RJ45 PoE port(POWER+DATA OUT) 1 power socket(DC IN)
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 1000BASE-T: UTP category 5, 5e, 6 cable(maximum 100m)
Basic Function	Auto-Sensing Algorithm enables providing power with 802.3af PD Delivers power and data over the single cable up to 100 meters Auto-determine the necessary power requirements Plug-and-Play
Power	Input: External 48VDC power adapter Output: Auto-determine the necessary Power requirements(max. 15.4W)
LED Indicator	ON: Supplying power normally Flashing: NO PD connected/Supplying power abnormally Off: No power supply
Dimensions (W x D x H)	80.8 x 54 x 24mm
Certification	FCC, CE, RoHS
Package Contents	TL-POE150S, Power Adapter, RJ45 cable, Installation Guide
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90%RH non-condensing Storage Humidity: 5%~90%RH non-condensing

Package:

- TL-POE150S PoE Injector
- One Ethernet (CAT.5 UTP) Cable
- One Power Adapter
- User Guide

Related Products:

- Load Balance Broadband Router
TL-R470T+
- AC750 Wireless Gigabit Access Point
AP200
- PoE Splitter
TL-POE10R

www.tp-link.com

Specifications are subject to change without notice. TP-Link is a registered trademark of TP-Link Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. Copyright © 2017 TP-Link Technologies Co., Ltd. All rights reserved.