

A refinement in outdoor interconnectivity

The HD1 Dome Pro adapts to the flexible nature of outdoor deployments, offering powerful speeds, with refined Wi-Fi options. The **5G modem**, with its **embedded cellular antennas**, ensures minimal cable loss and offers the finest signal quality.



Wi-Fi as **WAN**

\//i Ei 6

The **Wi-Fi 6** and **Wi-Fi as WAN** support can optimize your network and provide versatility as and when required. Leverage bandwidth costs and easily expand your network. Experience no more interruptions with SpeedFusion's hot failover options.





Instant flexibility with the SIM injector.

Simply connect an Ethernet cable between the SIM injector^ and the HD1 Dome Pro to manage up to **10 physical SIMs**.

With remote network management available via Peplink's cloud-based management system, InControl2, accessibility worries are a thing of the past.

SIM Injector Specifications

SIM Slots 8x Active SIM Slots, Standard Size

LAN Interface 4x GE, PoE 802.3at Support

Power Input DC Jack / Terminal Block: 12-56V

Dimensions 1.6 x 5.8 x 5 inches / 40 x 147 x 128 mm

Weight

430 grams / 0.94 pounds

Operating Temperature

Humidity

-40 - 149 °F / -40 - 65 °C

15% - 95% (non-condensing)



^We are now offering bundle value when purchased together. Contact your point of sales for more information.



Together it works

The HD1 Dome Pro can **optimize network performance** with its PoE functionality. Leverage the power of SpeedFusion by simply connecting Peplink PoE routers, for a mega-bandwidth channel, with the simplest failover option. Or alternatively, extend the Wi-Fi range by connecting an external access point.



A design that's made to meet your needs










M35 Screw Mount Etherne

Ethernet Splitter

Mounting Bracket

It's simple design offers a multitude of installation options. The HD1 Dome Pro includes an M35 screw mount and Ethernet splitter, making it easy for wall or pole mount. If mounting is not needed, simply connect an Ethernet cable and it's good to go.





Specifications

Number of

Antenna

Power Output

SpeedFusion VPN

WAN Interface 1x 5G Modem with Redundant SIM Slots ¹ Power	Consumption 20 W (max., without PoE output)
-------------------------------------------------------------------------------------	----------------------------------------------------

LAN Interface	1x 10/100/1000M Ethernet ^{2 3}	Dimension	4.33 inches (radius) x 4.53 inches (height)
---------------	-----------------------------------------	-----------	---------------------------------------------

Wi-Fi Interface Simultaneous Dual-Band (2.4GHz / 5GHz) 110 mm (radius) x 115 mm (height)

Wi-Fi 6, 2X2 MIMOWeightWith Ethernet Splitter:Wi-Fi WAN and/or AP3.75 pounds / 1.7 kg

Without Ethernet Splitter: 2.65 pounds / 1.2 kg

Peers Operating Temperature -40° – 149°F / -40° – 65°C

Enclosure Rugged outdoor IP67 (with Ethernet **Humidity** 15% – 95% (non-condensing) Splitter)

Certifications FCC, CE, RoHS⁴,

Recommended Users 150 Electromagnetic Compatibility: EN 61000³

Cellular Data Rate5G: 4 Gbps / 700 MbpsPackage ContentMAX HD1 Dome Pro,(Downlink / Uplink)LTE CAT-20: 2 Gbps / 150 MbpsEthernet Splitter,

2x Waterproof Ethernet Connector (ACW-112),

4X4 Internal MIMO Cellular Antennas Mounting Kit Set 2X2 Internal MIMO Wi-Fi Antennas

1x Internal GPS Antenna SIM Card Size Nano-SIM (4FF)

Power Input 1x 802.3at PoE+ **Warranty** 1-Year Limited Warranty

1x 802.3af PoE (with Ethernet Splitter)

¹SIM Injector is available separately.

² Ethernet LAN port can be split into two LAN ports using the included splitter (1x LAN 802.3af PoE out, 1x LAN 802.3at PoE+ in).

³ Ethernet port includes surge and ESD protection circuits to protect against over-voltage transients.

⁴Certification Pending.



Ordering Information

Product Code

MAX-HD1-DOM-PRO-5GD Embedded Modem(s): 1x 5G

Regions

Primary: APAC, EMEA Compatibility: Global

5G Bands

5G (NSA) Sub 6Ghz: n1, n2, n3, n5, n7, n8, n12, n20, n28, n38, n41, n66, n71, n77, n78, n79

LTE Bands

B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B46, B48, B66, B71

MAX-HD1-DOM-PRO-5GH

Embedded Modem(s): 1x 5G

Primary: North America* Compatibility: Global

*US Carrier Certifications: AT&T, FirstNet, T-Mobile(Pending), Verizon(Pending)

5G (NSA) Sub 6Ghz:

n1, n2, n3, n5, n28, n41, n66, n71, n77, n78, n79

B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B46, B48, B66, B71

Featured Add-on

Product Code


SIM-BK8-4E-56V-DOM

Description


MAX HD1 Dome Pro Bundle Offer - SIM Injector , 8x SIM cards capacity, 4x 10/100/1000 LAN ports, 56V DC




Cellular Antenna VSWR



Cellular Antenna Gain




Cellular Antenna Efficiency







Wi-Fi Antenna VSWR



Wi-Fi Antenna Gain





Wi-Fi Antenna Efficiency








LTE Radiation Patterns (Azimuth)





















LTE Radiation Patterns (Elevation 1)





















LTE Radiation Patterns (Elevation 2)



















Wi-Fi Radiation Patterns (Azimuth)

2400-2500 MHz



Wi-Fi Radiation Patterns (Elevation 1)





Wi-Fi Radiation Patterns (Elevation 2)

